

## Features

1. Uncoiler and straightener two in one style improves factory usable space.
2. Straightening adopts the balance adjusting equipment and suitable for processing higher precision products.
3. Roller adopts the solid bearing steel and hard chrome plating treatment .

## Technical parameters

Model	Max width	Thickness	Max weight	Inner diameter	Outer diameter	Straighening roller	Motor	Stacking style
TGL-300	300mm	0.5-3.2mm	2000kg	450-530mm	1200mm	Φ60x7	1.5kw/4p	Manual/Hydraulic
TGL-400	400mm	0.5-3.2mm	3000kg	450-530mm	1200mm	Φ60x7	2.2kw/4p	Manual/Hydraulic
TGL-500	500mm	0.5-3.2mm	3000kg	450-530mm	1200mm	Φ60x7	2.2kw/4p	Manual/Hydraulic
TGL-600	600mm	0.5-3.2mm	3000kg	450-530mm	1200mm	Φ60x7	2.2kw/4p	Manual/Hydraulic
TGL-700	700mm	0.5-3.2mm	4500kg	450-530mm	1200mm	Φ60x7	3.7kw/4p	Manual/Hydraulic
TGL-800	800mm	0.5-3.2mm	5000kg	450-530mm	1200mm	Φ60x7	3.7kw/4p	Manual/Hydraulic
TGL-300A	300mm	0.5-4.5mm	2000kg	450-530mm	1200mm	Φ75x9	1.5kw/4p	Manual/Hydraulic
TGL-400A	400mm	0.5-4.5mm	3000kg	450-530mm	1200mm	Φ75x9	1.5kw/4p	Manual/Hydraulic
TGL-500A	500mm	0.5-4.5mm	3000kg	450-530mm	1200mm	Φ75x9	1.5kw/4p	Manual/Hydraulic
TGL-600A	600mm	0.5-4.5mm	4500kg	450-530mm	1200mm	Φ75x9	2.2kw/4p	Manual/Hydraulic
TGL-700A	700mm	0.5-4.5mm	4500kg	450-530mm	1200mm	Φ75x9	2.2kw/4p	Manual/Hydraulic
TGL-800A	800mm	0.5-4.5mm	5000kg	450-530mm	1200mm	Φ75x9	3.7kw/4p	Manual/Hydraulic

## Straightening capacity

Model	TGL-300A	TGL-400A	TGL-500A	TGL-600A	TGL-700A	TGL-800A
2.5mm(thickness)	300	400	500	600	700	800
3.0mm(thickness)	300	400	500	600	700	800
3.5mm(thickness)	300	400	500	500	550	600
4.0mm(thickness)	300	400	400	400	400	420