

Performance Feature

1. Apply to precision electronic component punch in large quantity
2. Enhance life if punch and mold under power balance device
3. Oil-ressure slider fixed locking and sticking release device can increase reliability
4. Cylinder connecting rod driving device can enhance of punch's operation and precision

Technical parameters

Name		APL-25			APL-45			API-65		
Model		A	B	C	A	B	C	A	B	C
Capacity	ton	25			45			65		
Rated tonnage point(B.D.C)	mm	1.2			1.2			1.6		
Stroke	mm	20	30	40	20	30	40	20	30	40
Stroke per minute	s.p.m	100-600	100-500	100-400	100-500	100-400	100-300	100-400	100-350	100-300
Die height	mm	225	220	215	265	260	255	305	300	295
Bolster area(L.R.xF.B.)	mm	650x390x75			760x450x90			860x52x100		
Slide area(L.R.xF.B.)	mm	280x250			380x320			460x370		
Slide adjustment	mm	30			30			50		
Main motor	Kw	3.7x4P			5.5x4P			7.5x4P		
Shank hole	mm	Φ38.1			Φ50			Φ50		
Hole of bed (L.R.Xf.B.)	mm	270x150			400x200			480X260		
Lubrication system		Forced Recirculating Lubrication								