

High Speed Precision Slitting Line For Thick Plate



Specification:

No.	Model	Raw Material	THK (mm)	Width (mm)	ID (mm)	OD (mm)	Weight (T)	Width accuracy (mm)	Slit No. (pcs)	Slitting width (mm)	Speed (m/min)	Capacity (kw)	Flood space (m*m)
1	4.0x1600	carton steel, stainless steel, aluminum or other steel material	0.5-4.0	800-1600	Φ508/610	≤Φ1500	≤25	≤±0.1	≤24	≥30	≤120	≈220	25x7.5
2	6.0x800		1.0-6.0	200-800	Φ508/610/760		≤15		≤24	≥30	≤60	≈220	15x5.5
3	6.0x1600		1.0-6.0	800-1600			≤25		≤24	≥40	≤50	≈220	28x10.5
4	9.0x1600		2.0-9.0	800-1600	≤Φ2000	≤25	≤12	≥60	≤40	≈265	28x10		
5	12x2000		3.0-12.0	1000-2000		≤35	≤±0.5	≤10	≥200	≤20	≈285	36x10	
6	16x2200		4.0-16.0	1000-2200		≤35		≤10	≥200	≤20	≈285	36x10	

PS: All above specifications only for reference, also can customize as your request.